

512

HIGH PERFORMANCE TROMMEL

The 512 screeners provide McCloskey[™] customers with the functionality of our highly successful trommel line-up. The 512 Trommels are best suited for mid-size operations requiring portability and proven screening performance.

As the top selling mid-size portable trommel in North America, the 512 offers a combination of high production rates, versatility, ease of use and unrivalled strength that has ensured this screener's popularity with top soil producers, contractors, and landscape supply operators.

Our 512 range of models include the 512A wheeled unit with an extended fines conveyor, the 512R (wheeled) and 512RT (tracked) with our patented radial conveyor, and our 512RET that has been specially designed with compact transport dimensions for cost efficient ocean shipping.

(See reverse for specifications)



512RT shown with optional Tipping Grid & Spill Plate


HOPPER CAPACITY Hopper capacity of 4.5yd³ - 7.0yd³ with extensions for greater efficiency.






DRUM DRIVE Solid vulcanized, independently powered drive wheels for maximum torque, traction and life.

BRUSHES Ground level adjustable brushes keep the screen clean and rotate away from drum for ease of drum change.





LIFTING BARS Deep lifting bars on drum provide aggressive screening action.

RADIAL CONVEYOR

Patented radial conveyor with 180° swing and variable discharge height for maximum stockpiling flexibility.



McCloskey International reserves the right to make changes to the information and design of the machines on this brochure without reservation and notification to the users. Information at time of print considered accurate — McCloskey International assumes no liability resulting from errors or omissions in this document.

mccloskeyinternational.com



512A

Engine	74 Hp (55 kW) Diesel
Stockpile Height	9′0″ (2.74m)
Transport Height	12′1″ (3.69 m)
Transport Length	42′ 2″ (12.85 m)
Transport Width	8′6″ (2.59 m)
Weight	21,500 lb (9,750 kg)





512R

Engine	74 Hp (55 kW) Diesel
Stockpile Height	15' 3.5" (4.66 m)
Transport Height	13'6" (4.11 m)
Transport Length	47' 10.5" (14.60 m)
Transport Width	8′6″ (2.59 m)
Weight	27,000 lb (12,250 kg)

512RT

Engine	74 Hp (55 kW) Diesel
Stockpile Height	12′ 10.5″ (3.92 m)
Transport Height	11′7″ (3.53 m)
Transport Length	46' 1.5" (14.06 m)
Transport Width	8′6″ (2.59 m)
Weight	40,000 lb (18,140 kg)





McCloskey International reserves the right to make changes to the information and design of the machines on this brochure without reservation and notification to the users. Information at time of print considered accurate — McCloskey International assumes no liability resulting from errors or omissions in this document.

512RET

Engine	74 Hp (55 kW) Diesel
Stockpile Height	11'8" (3.55 m)
Transport Height	10'8" (3.30 m)
Transport Length	35' (10.70 m)
Transport Width	8′ 2.5″ (2.50 m)
512RET Weight	42,500 lb (19,280 kg)

mccloskeyinternational.com