# McCloskey



## **High Production Jaw Crusher**

The McCloskey™ J45 high capacity Jaw Crushers feature a true 45" x 27" jaw. With both level and load sensors the J45 ensures the most efficient material handling across applications. Optimized for Type 1 crushing applications, the J45 features a heavy duty bofor design and transfer chutes with steeper angles to reduce material sticking.

The J45 boasts a high capacity hopper with close to 8

cubic yards (6m³) capacity mounted over a vibrating feeder. The main conveyor features easy access heavy duty skirting and is closer to the ground level for ease of access and maintenance.

Rugged and versatile, the J45 offers field-tested reliability required for the toughest projects around the globe.

### **Features**

- 1140 (45") x 688 (27") single toggle jaw
- Track or Track c\w Wheel bogie
- Integrated hydraulic folding hopper
- Integrated hydraulic folding stockpiling conveyors
- I-beam plate fabricated chassis construction
- Large gap between crusher discharge and main conveyor feedboot
- Open chassis design for ease of maintenance
- Fast setup time

# McCloskey

#### **Feeder**

Folding hopper mounted over vibrating feeder with integral pre-screen. Feeder rate can be regulated manually or automatically by load sensing jaw.

**Control Panel** 

User friendly waterproof and dustproof control panel. Allows monitoring of pressures, fluid levels and fuel consumption. Provides push button control of jaw, track and feeder functions.

#### 42" Extended Conveyor

Extended 42" main conveyor as standard, giving large stockpile capacity. Conveyor lowers and raises hydraulically.

between job sites.



#### **Crusher Pre-screen**

Optional independent crusher pre-screen maximizes crusher efficiency and delivers screened product via side conveyor.

#### **Jaw Crusher**

True 45" x 27" jaw with reversible hydrostatic drive, reversible jaw plates, and twin hydraulic ram wedge closed side setting (CSS) adjust.

#### mccloskeyinternational.com

#### **SPECIFICATION DATA**

#### **Dimensions and Capacities**

Engine 350 Hp (261 kW)

Diesel

Transport Height 11' 1.8" (3.40m)

Transport Length 47' 5.9" (14.48m)

Transport Width 8' 2.5" (2.50m)

Weight - w/ magnet 99,208 lb & side conveyor (45,000kg)

Crushing Chamber 45"(wide) x 27"

(pitman opening)

Stockpile Height Main Conveyor

12' 8.7" (3.88m)

Stockpile Height

8' 2.3" (2.50m)

Side Conveyor

Optional Prescreen 41.9" x 75.5"

Feeder

(1.06m x 1.92m)

©Copyright 2020 McCloskey International.

All rights reserved. McCloskey is a trademark of McCloskey International.

McCloskey International reserves the right to make changes to the information and design of the machines on this brochure without reservation and notification to the users. Information at time of print considered accurate — McCloskey International assumes no liability resulting from errors or omissions in this document.