













Features of the M412

- Feed Rocks up to 600mm (24")
- Output of up to 300 TPH
- Fuel Consumption 7l per hour
- Welded Drum or Changeable screens
- · Hydraulic Push feeder
- Variable Drum Speed: 8-12 RPM
- Fines up Screens up to 200mm (8")
- Heavy Duty Belts
- 3m (9' 11") Transport Height
- Tipping Grid Option Available
- Drum Cleaner Option
- Hopper capacity: 4 cubic metre capacity (141ft3)
- Drum Lengths: 4m (13 ft 1") long, 1250mm (4 ft 1"), Internal Dia

Oversize : 2657mm (8 ft 9") Fines : 2340mm (7 ft 8")

Transport Dimensions:

 Length
 :
 12836mm
 (42 ft 1")

 Width
 :
 2500mm
 (8 ft 2")

 Height
 :
 3000mm
 (9 ft 10")

3419mm (11 ft 3") with Grid

Weight : 21.5 Tonnes (23.7 US Tons)



Features of M413

- Feed Rocks up to 600mm (24")
- 3 Splits Trommel
- Output of Up to 300 TPH
- Fuel Consumption 7l per hour
- Welded Drum or Changeable screens
- •Hydraulic Push feeder
- •Fines Screens up 200mm (8")
- •Mid Product screens up to 250mm (10")
- Heavy Duty Belts
- 3m (9' 11") Transport Height
- •Tipping Grid Option
- •Drum Cleaner Option
- •Variable Drum Speed: 8-12 RPM
- Hopper Capacity: 4 cubic metre capacity (141ft3)
- •Drum Lengths 4m (13 ft 1") long 1250mm (4 ft 1") diameter
- •Oversize : 2342mm (7 ft 8")

Mid-Product :2355mm (7 ft 9") Fines: 2203mm (7 ft 2")

Transport Dimensions:

 Length
 :
 12841mm
 (42 ft 2")

 Width
 :
 2500mm
 (8 ft 2")

 Height
 :
 3100mm
 (10 ft 2")

3419mm (11 ft 3") with Grid

Weight : 24 Tonnes (26.5 US Tons)





Features of M515

- Feed Rocks up to 800mm (32")
- Output of Up to 500 TPH
- Fuel Consumption 15l per hour
- 3 Splits Trommel
- Adjustable Height on Jack Legs
- Welded or Changeable screens
- Hydraulic Push feeder
- Variable Drum Speed: 8-12 RPM
- Fines up 200mm (8")
- Mid Product up to 450mm (18")
- Heavy Duty US Flex Belts
- Tipping Grid Option
- Drum Cleaner Option
- Hopper capacity 12 cubic metre capacity (423ft3)
- Drum Lengths 5.5m (18ft) long with 2 sections, 1500mm (4ft11") Internal diameter

Transport Dimensions:

Length: 17047mm (55 ft 11") Width: 2980mm (9 ft 9")

3214mm (10 ft 7") with Grid

Height: 3500mm (11 ft 6")

3214mm (10 ft 7") with Grid

Weight: 48 Tonnes (52.9 US Tons)

Oversize : 3576mm (11 ft 9") Mid Product : 3358mm (11 ft 0") Fines : 3850mm (12 ft 8")





Features of M615

- Feed Rocks up to 800mm (32")
- Output of Up to 500 TPH
- Fuel Consumption 15l per hour
- Can have up to 4 Splits
- Concrete or Steel Base Option
- Welded or Changeable screens
- Hydraulic Push feeder
- Variable Drum Speed: 8-12 RPM
- 20 Ton Hopper Option
- Drum with up to 600mm (24") openings
- Tipping Grid Option
- Drum Cleaner Option
- Hooper Capacity MAX 800mm/32"
- Drum lengths: 1.5m (4 ft 11") Drum Diameter
 6m (19ft 8") Drum Length
 Drum Cleaner Option Available
 4 Outputs (5 with Grid

Transport Dimensions:

Length: 12323mm (40 ft 0") Width: 2556mm (8 ft 5") Height: 3036mm (9 ft 12")

Weight: 35 Tonnes (38.6 US Tons)





Features of M820

- Feed Rocks up to 1000mm (40")
- Output of Up to 750 TPH
- Fuel Consumption 30l per hour
- Can give Up to 4 Splits
- Track, Concrete or Steel Base
- Welded Drum or Changeable screens
- Hydraulic Push feeder
- Drum Openings up to 750mm (30")
- 40 Ton Hopper Option
- Drum Cleaner Option
- Variable Drum Speed: 8-12 RPM
- Feeders available on tracks
- Hopper capacity: MAX 1000mm/40"
- Drum lengths: 2m (6ft 7") Diameter

8m (26 ft 3") length

3 or 4 outputs (50 to 600mm / 2-24in)

5 with Tipping Grid

Transport Dimensions:

Length : 14923mm (49 ft 0")

 Width
 :
 3884mm
 (12 ft 9")

 Height
 :
 3837mm
 (12 ft 7")

Static Weight : 70 Tonnes (77.2 US Tons) With Tracks : 155 Tonnes (170.9 US Tons)

