



CLASSIFYING TANK

Ideally Suited for Producing Sand with Excessive Water, High Silt or a "Belly" in the Grading



FEATURES

- » High pressure hydraulics quickly open and close valves for precise spec
- » Patented Aggrespec® Control System is easy to use
- » Weir to weir tank measurements offer highest holding capacity in industry
- » Stationary, semi-portable and portable models

APPLICATIONS

- » Production of construction aggregates
- » Convert variable, out-of-spec feed to in-spec
- » Produce three uniform products from single feed
- » Scalp excess water for efficient dewatering





01/ HIGH CAPACITY TANK

From weir to weir, our measurements equal the industry's highest capacity tank.

02/ SLOPED FEEDBOX

Slanted design promotes better flow of material to tank.

03/ AR LINING

Standard abrasion resistant steel lining shields feedbox and trough from wear.

04/ URETHANE WEAR PARTS

Valves, seats and discharge elbows are constructed of wear resistant polyurethane.

05/ SUPPORT STRUCTURE

Robust Superior design can be customized to incorporate other processing equipment.

06/ WALKWAY/STAIRS

Compared to ladders, stairs and walkways offer simple, safe access to tank components.

07/ ELEVATED VALVE BRIDGE

Raised at least 4" (101mm) more than competitors to prevent water from damaging mechanical parts.

08/ HINGED WALKWAY PLATES

Easily swing open to access mechanical valve stations below walkway.

09/ ADJUSTABLE WEIR

Adjust up or down to maximize fines retention.

10/ RECIRCULATING PUMP

Recycles water that spills over the weirs back into the tank.

11/ RISING CURRENT CELLS

Adjustable system prevents lighter materials from settling into first few stations for better efficiency.

HIGHLIGHTS



04/ URETHANE DISCHARGE VALVES



07/ ELEVATED VALVE BRIDGE



08/ HINGED WALKWAY PLATES



10/ RECIRCULATING PUMP

MODELS



STATIONARY

- » 8' x 20' to 12' x 48'
- » (2.4m x 6.0m) to (3.6m x 14.6m)
- » Single or double tanks
- » 6-22 stations
- » Valve bridge walkway with railings
- » AR lined blending flumes and feedboxes
- » Urethane valves, seats and discharge elbows
- » Self-Aligning valves and seats
- » Onsite spec testing and control system training



SEMI-PORTABLE

- » 8' x 24' to 12' x 48'
- » (2.4m x 7.3m) to (3.6m x 14.6m)
- » Skid-mounted, modular design
- » 7-11 stations
- » Aggredry® Washer or Fines Material Washer
- » Produce (2) individual products or
- » Produce maximum primary product
- » Prewired plant



PORTABLE

- » 8' x 24' to 10' x 40'
- » (2.4m x 7.3m) to (3.0m x 12.1m)
- » Fifth wheel hitch
- » 7-11 stations
- » Aggredry® Washer or Fines Material Washer
- » Air brakes
- » Lights
- » Hydraulic leveling jacks
- » Prewired plant

AGGRESPEC® CONTROL SYSTEMS



AGGRESPEC® III CONTROL SYSTEM

- » Microsoft Windows-based control system is familiar and easy to use
- » Up to 15% more productivity than single method programs
- » Automatically create and maintain tight specifications
- » Control from remote location (i.e. home or office)
- » Store and recall unlimited number of mixes
- » Program automatic tank cleanout
- » Patented twin tank control operates up to 22 stations
- » Retrofit to competitor tanks



AGGRESPEC® I CONTROL SYSTEM

- » Operate from simplified PLC panel
- » Touch screen
- » Manual calculations directs product in tank
- » Monitor and adjust essential parameters


PHOTO GALLERY



HINGED WALKWAY PLATES



HYDRAULIC HOSES



BRIDGE GAP PROTECTS MECHANICS

STATIONARY CLASSIFIER SPECIFICATIONS

Tank Size ft (m)	Stations	Estimated Tank Weight lbs. (kg)	Estimated Support Structure Weight* lbs. (kg)	Water Capacity GPM (m ³ /hr)		
				100 Mesh (150 µm)	150 Mesh (113 µm)	200 Mesh (75 µm)
Single Tank						
8' x 20' (2 x 6)	6	12,000 (5,443)	12,440 (5,643)	2,300 (522)	1,200 (272)	N/A
8' x 24' (2 x 7)	7	14,000 (6,350)	12,840 (5,824)	2,800 (635)	1,400 (318)	N/A
8' x 28' (2 x 9)	8	16,000 (7,258)	13,000 (5,897)	3,200 (726)	1,600 (363)	N/A
8' x 32' (2 x 10)	9	18,000 (8,165)	14,180 (6,432)	3,500 (794)	1,800 (408)	N/A
10' x 24' (3 x 7)	7	18,000 (8,165)	13,800 (6,260)	3,500 (794)	1,800 (408)	N/A
10' x 28' (3 x 9)	8	20,000 (9,072)	14,000 (6,350)	4,100 (931)	2,100 (477)	N/A
10' x 32' (3 x 10)	9	24,000 (10,886)	15,200 (6,895)	4,700 (1,067)	2,400 (545)	1,250 (283)
10' x 36' (3 x 11)	10	28,000 (12,701)	16,500 (7,484)	5,300 (1,204)	2,700 (613)	1,400 (318)
10' x 40' (3 x 12)	11	30,000 (13,608)	18,000 (8,165)	5,900 (1,340)	3,000 (681)	1,500 (340)
12' x 48' (4 x 15)	11	44,000 (19,958)	23,600 (10,705)	8,100 (1,840)	4,200 (953)	2,150 (488)
Double Tank						
10' x 32' (3 x 10)	9	48,900 (22,181)	30,300 (13,744)	9,400 (2,135)	4,800 (1,090)	2,500 (567)
10' x 36' (3 x 11)	10	53,000 (24,040)	32,700 (14,833)	10,600 (2,408)	5,400 (1,226)	2,800 (635)
10' x 40' (3 x 12)	11	56,000 (25,401)	35,200 (15,967)	11,800 (2,680)	6,000 (1,363)	3,000 (681)
12' x 48' (4 x 15)	11	86,000 (39,009)	48,200 (21,863)	16,200 (3,679)	8,400 (1,908)	4,300 (976)

*One chute, one walkway and one stairs

SEMI-PORTABLE CLASSIFIER SPECIFICATIONS

Tank Size ft (m)	Stations	Estimated Weight lbs. (kg)	Screw Size in x ft (mm x m)	Capacity TPH (MTPH)	Water Capacity GPM (m ³ /hr)		
					100 Mesh (150 μm)	150 Mesh (113 μm)	200 Mesh (75 μm)
Semi-Portable Classifier with Fine Material Washer - Triple Flume							
8' x 24' (2 x 7)	7	40,000 (18,143)	Twin 36" x 25' (914 x 7)	200 (181)	2,800 (635)	1,400 (318)	N/A
8' x 28' (2 x 9)	8	42,000 (19,050)	Twin 36" x 25' (914 x 7)	200 (181)	3,200 (726)	1,600 (363)	N/A
8' x 32' (2 x 10)	9	48,500 (21,999)	Twin 36" x 25' (914 x 7)	200 (181)	3,500 (794)	1,800 (408)	N/A
10' x 24' (3 x 7)	7	50,000 (22,679)	Twin 36" x 25' (914 x 7)	200 (181)	3,500 (794)	1,800 (408)	N/A
10' x 28' (3 x 9)	8	51,000 (23,133)	Twin 36" x 25' (914 x 7)	200 (181)	4,100 (931)	2,100 (477)	N/A
10' x 32' (3 x 10)	9	51,500 (23,360)	Twin 36" x 25' (914 x 7)	200 (181)	4,700 (1,067)	2,400 (545)	1,250 (283)
10' x 36' (3 x 11)	10	58,500 (26,535)	Twin 36" x 25' (914 x 7)	200 (181)	5,300 (1,204)	2,700 (613)	1,400 (318)
10' x 40' (3 x 12)	11	63,000 (28,576)	Twin 36" x 25' (914 x 7)	200 (181)	5,900 (1,340)	3,000 (681)	1,500 (340)
8' x 32' (2 x 10)	9	60,000 (27,216)	Twin 44" x 32' (1,118 x 10)	350 (318)	3,500 (794)	1,800 (408)	950 (215)
10' x 32' (3 x 10)	9	64,500 (29,257)	Twin 44" x 32' (1,118 x 10)	350 (318)	4,700 (1,067)	2,400 (545)	1,250 (283)
10' x 36' (3 x 11)	10	67,000 (30,391)	Twin 44" x 32' (1,118 x 10)	350 (318)	5,300 (1,204)	2,700 (613)	1,400 (318)
10' x 40' (3 x 12)	11	68,000 (30,844)	Twin 44" x 32' (1,118 x 10)	350 (318)	5,900 (1,340)	3,000 (681)	1,500 (340)
10' x 40' (3 x 12)	11	97,000 (43,999)	Twin 54" x 35' (1,372 x 11)	550 (500)	5,900 (1,340)	3,000 (681)	1,500 (340)
10' x 40' (3 x 12)	11	132,000 (59,874)	Twin 66" x 35' (1,676 x 11)	800 (725)	5,900 (1,340)	3,000 (681)	1,500 (340)
12' x 48' (4 x 15)	11	91,000 (41,277)	Twin 44" x 32' (1,118 x 10)	350 (318)	8,100 (1,840)	4,200 (953)	2,150 (488)
12' x 48' (4 x 15)	11	116,000 (52,617)	Twin 54" x 35' (1,372 x 11)	550 (500)	8,100 (1,840)	4,200 (953)	2,150 (488)
12' x 48' (4 x 15)	11	150,000 (68,039)	Twin 66" x 35' (1,676 x 11)	800 (725)	8,100 (1,840)	4,200 (953)	2,150 (488)
12' x 48' (4 x 15)	11	175,000 (79,379)	Twin 72" x 35' (1,829 x 11)	950 (861)	8,100 (1,840)	4,200 (953)	2,150 (488)
Semi-Portable Classifier with Aggredry® Dewatering Washer							
8' x 24' (2 x 7)	7	54,000 (24,494)	Twin 36" (914)	200 (181)	2,800 (635)	1,400 (318)	N/A
8' x 28' (2 x 9)	8	56,000 (25,401)	Twin 36" (914)	200 (181)	3,200 (726)	1,600 (363)	N/A
8' x 32' (2 x 10)	9	62,500 (28,350)	Twin 36" (914)	200 (181)	3,500 (794)	1,800 (408)	N/A
10' x 28' (3 x 9)	7	64,000 (29,030)	Twin 36" (914)	200 (181)	4,100 (931)	2,100 (477)	N/A
10' x 32' (3 x 10)	8	65,000 (29,483)	Twin 36" (914)	200 (181)	4,200 (953)	2,400 (545)	1,250 (283)
10' x 36' (3 x 11)	9	65,500 (29,710)	Twin 36" (914)	200 (181)	5,300 (1,204)	2,700 (613)	1,400 (318)
10' x 40' (3 x 12)	10	72,500 (32,885)	Twin 36" (914)	200 (181)	5,900 (1,340)	3,000 (681)	1,500 (340)
8' x 32' (2 x 10)	9	78,000 (35,380)	Twin 48" (1,219)	400 (363)	5,300 (1,204)	1,800 (408)	950 (215)
10' x 32' (3 x 10)	9	82,500 (37,421)	Twin 48" (1,219)	400 (363)	4,700 (1,067)	2,400 (545)	1,250 (283)
10' x 36' (3 x 11)	10	85,000 (38,555)	Twin 48" (1,219)	400 (363)	5,300 (1,204)	2,700 (613)	1,400 (318)
10' x 40' (3 x 12)	11	86,000 (39,009)	Twin 48" (1,219)	400 (363)	5,900 (1,340)	3,000 (681)	1,500 (340)
10' x 40' (3 x 12)	11	140,000 (63,503)	Twin 66" (1,676)	800 (725)	5,900 (1,340)	3,000 (681)	1,500 (340)
12' x 48' (4 x 15)	11	109,000 (49,442)	Twin 48" (1,219)	400 (363)	8,100 (1,840)	4,200 (953)	2,150 (488)
12' x 48' (4 x 15)	11	158,000 (71,668)	Twin 60" (1,524)	600 (544)	8,100 (1,840)	4,200 (953)	2,150 (488)

FULLY-PORTABLE CLASSIFIER SPECIFICATIONS

Tank Size ft (m)	Stations	Estimated Weight lbs. (kg)	Screw Size in x ft (mm x m)	Capacity TPH (MTPH)	Axle/Tires	Water Capacity GPM (m ³ /hr)		
						100 Mesh (150 µm)	150 Mesh (113 µm)	200 Mesh (75 µm)
Fully Portable Classifier with Fine Material Washer - Triple Flume								
8' x 24' (2 x 7)	7	50,000 (22,679)	Twin 36" (914)*	200 (181)	2/8 or 3/12	2,800 (0.17)	1,400 (0.08)	N/A
8' x 28' (2 x 9)	8	51,000 (23,133)	Twin 36" (914)*	200 (181)	2/8 or 3/12	3,200 (0.20)	1,600 (0.10)	N/A
8' x 32' (2 x 10)	9	52,000 (23,587)	Twin 36" (914)*	200 (181)	2/8 or 3/12	3,500 (0.22)	1,800 (0.11)	950 (0.05)
8' x 32' (2 x 10)	9	73,500 (33,339)	Twin 44" (1,118)*	350 (318)	3/12	3,500 (0.22)	1,800 (0.11)	950 (0.05)
10' x 28' (3 x 9)	8	81,000 (36,741)	Twin 44" x 32' (1,118 x 10)	350 (318)	3/12	4,100 (0.25)	2,100 (0.13)	N/A
10' x 32' (3 x 10)	9	86,000 (39,009)	Twin 44" x 32' (1,118 x 10)	350 (318)	3/12	4,700 (0.29)	2,400 (0.15)	1,250 (0.07)
10' x 36' (3 x 11)	10	88,000 (39,916)	Twin 44" x 32' (1,118 x 10)	350 (318)	3/12	5,300 (0.33)	2,700 (0.17)	1,400 (0.08)
10' x 40' (3 x 12)	11	95,000 (43,091)	Twin 44" x 32' (1,118 x 10)	350 (318)	3/12	5,900 (0.37)	3,000 (0.18)	1,500 (0.09)

*Screw length dependant of number of axles required therefore will be 25-ft, 28-ft or 30-ft