

# UL4853

## HIGH POWER WHEELED UNLOADER

The new UL4853 truck unloader has been developed and designed specifically for bulk material handling applications. The UL4853 easily takes loads from a low base and conveys a large volume of material efficiently, eliminating double handling through direct unloading of trucks.

The 48" x 53' conveyor belt loads material onto a stock-pile, into a barge or rail carriage, or other auxiliary equipment, delivering up to 1500 US TPH. The truck unloader has the ability to handle a complete range of materials such as; coal, sand, gravel, grains, ores (iron, copper, tin, bauxite, etc.), aggregates, woodchips, and more.



### 48" MAIN CONVEYOR

Heavy duty main 48" wide conveyor and 53' long offers hydraulic folding for easy transport.



### LARGE FEED HOPPER

Steel hopper allows operators to load 2.3m<sup>3</sup> of standard aggregates with a double-sided hopper option.

### HYDRAULIC FOLDING CONVEYOR

Straight forward hydraulic controls to fold and unfold, raise and lower conveyor for easy transport.



### ACCESSIBLE

Controls are groundlevel, delivering easy access for maintenance and service.

### WHEELED MOBILITY

Fully portable wheeled or tracked (UL4853T) unit available, allowing for maximum on-site mobility.



Engine	74.5kW (100Hp)
Transport Height	3.52m (11' 6.5")
Transport Length	13.44m (44' 1")
Transport Width	2.59m (8' 6")
Weight	7,300kg (16,100 lbs)
Stockpile Height (@ 22°)	3.9m (12' 6")
Hopper Capacity	2.3m <sup>3</sup> (3.0 yd <sup>3</sup> )

# UL4853T


## HIGH POWER TRACKED UNLOADER

The new UL4853T truck brings power and productivity to bulk material handling applications. The UL4853T easily takes loads from a low base and conveys a large volume of material efficiently, eliminating double handling through direct unloading of trucks.

The wide, extended 48" x 53' conveyor belt loads material onto a stock-pile, into a barge or rail carriage, or other auxiliary equipment, delivering up to 1500 US TPH. The truck unloader has the ability to handle a complete range of materials such as; coal, sand, gravel, grains, ores (iron, copper, tin, bauxite, etc.), aggregates, woodchips, and more.

### 48" MAIN CONVEYOR

Heavy duty main 48" wide conveyor and 53' long offers hydraulic folding for easy transport.



### LARGE FEED HOPPER

Steel hopper allows operators to load 2.3m<sup>3</sup> of standard aggregates with a double-sided hopper option.

### HYDRAULIC FOLDING CONVEYOR

Straight forward hydraulic controls to fold and unfold, raise and lower conveyor for easy transport.



### ACCESSIBLE

Controls are groundlevel, delivering easy access for maintenance and service.

### TRACKED MOBILITY

Fully portable tracked or wheeled (UL4853) unit available, allowing for maximum on-site mobility.



Engine	74.5kW (100Hp)
Transport Height	3.52m (11' 6.5")
Transport Length	13.44m (44' 1")
Transport Width	2.59m (8' 6")
Weight	7,300kg (16,100 lbs)
Stockpile Height (@ 22°)	3.9m (12' 6")
Hopper Capacity	2.3m <sup>3</sup> (3.0 yd <sup>3</sup> )