

CR-155

HIGH CAPACITY LONG HOPPER SCREENER

The ER-155 High Energy Screener is a tough, robust screening tool designed to cope with the heaviest of applications. New for this ER-155 scalping screener, are longer hopper and an extended tail conveyor. This provides maximum load flexibility to customers and accommodates a larger variety of loaders and can work in a variety of sites around the world.

No More Slow Loading! The ER-155 is designed for use with larger loaders. The 16ft target is 25% larger, allowing for more material and no spillage, making this ER-155 an excellent mobile solution for materials handling operations.

FEATURES

 5' X 16' heavy duty high energy 2 bearing screenbox

R-155

- Trademark to HARDOX[™]
- Direct feed HARDOX[™] lined hopper
- Travel out fixed walkways
- Integrated hydraulic folding stockpiling conveyors
- Fast on site setup time 10 minutes
- Screen raises at lower end for easy bottom deck access
- Service standing room inside powerpack
- Track mobile



SPOKED TAIL PULLEYS

• Supplied as standard to avoid material build up.

FLEX-FLOW

Flex-Flow screens are built to take on the toughest materials,

model works in tandem with other on-site equipment. With their fast set-up time and ability to move around job sites, the suited to projects where

FRIENDLY

containerised, costs.

> • All guarding is fully compliant with CE specifications.

RADIAL AXLE

OVER CENTRE VALVES

• Reduces set-up time.

• Pivoting axle box allows for creating swept radius stockpiles.

DIMENSIONS AND CAPACITIES

ENGINE	130 HP (98 KW) DIESEL	TRANSPORT WIDTH	9′ 8″ (3.54M)	STOCKPILE HEIGHT SIDE FINES CONVEYOR	13' (3.96M)
TRANSPORT HEIGHT	11' 7" (3.53M	WEIGHT	36,100 KGS (79,600 LBS)	STOCKPILE HEIGHT SIDE MID CONVEYOR	11' 10" (3.60M)
TRANSPORT LENGTH	50' 2" (15.30M)	STOCKPILE HEIGHT EXTENDED TAIL CONVEYOR	12′ 3″ (3.75M)	SCREENBOX DIMENSIONS	5' X 16' (155 FT²)

