

TRACKED RADIAL FEEDER STACKER

The EF-80R comprises of a large feeder hopper that transfers material onto an 80ft conveyor, all fitted to a slew ring assembly allowing for full 360° radial.

Designed to allow operators to stockpile/transfer material it eliminates double handling of materials. Its maneuverability makes this unit very versatile and makes it ideal for barge loading and unloading, rail loading / unloading and stockpiling, the ability to move parallel enables the operator to maneuver the unit parallel to the vessel meaning the machine can crab alongside.

The unit can also be compacted for transport on one low loader for easy site to site transport.

FEATURES

- CAT 4.4 100KW (127HP) engine
- Hydraulic folding heading section for transport minimizing setup time
- Hydraulically adjustable discharge height up to 10m
- Fuel efficient Hydraulics system
- 4m tracks for superior maneuverability and stability
- User Friendly Hydraulic Controls
- Dual hydraulic main drive system
- Remote near stabilizing legs for easy operator use
- Remote radio tracking
- Hopper extensions increasing capacity



80" MAIN CONVEYOR

 Heavy duty main 48" wide conveyor and 80' long offers hydraulic folding.

LARGE FEEDER

 Steel hopper allows operators to load 13m³ of standard aggregates with hopper extensions option to increase capacity.

INTUITIVE CONTROL PANEL

 Easy to use control panel makes operating the machine simple.

HYDRAULIC FOLDING CONVEYOR

 Straight forward hydraulic controls to fold and unfold, raise and lower conveyor for easy transport.

TRACKED MOBILITY

 Fully portable tracked unit with 4m wide tracks, allowing for maximum on-site stability.

DIMENSIONS AND CAPACITIES

| ENGINE | CAT 4.4 127 HP | OVERHANG TRANSPORT | 7.2M | STOCKPILE HEIGHT | 10M (32′ 10″) |
|------------------|----------------|--------------------|-------------------------------|-----------------------|---------------|
| TRANSPORT HEIGHT | 3.4M (11′ 1″) | WEIGHT | 27,500KG APPROX. (60,627 LBS) | HOPPER CAPACITY | 13M³ (17 YD³) |
| TRANSPORT LENGTH | 19.4M (38′ 8″) | WORKING MAX LENGTH | 6.2M | PRODUCTION RATE (MAX) | 800 TPH |
| TRANSPORT WIDTH | 3.2M (10′ 6″) | WORKING MAX HEIGHT | 10M | RADIAL | FULL 360° |

© Copyright 2021 McCloskey Environmental. All rights reserved. McCloskey is a trademark of McCloskey Internationa

McCloskey Environmental reserves the right to make changes to the information and design of the machines on this brochure without reservation and notification to the users. Information at time of print considered accurate — McCloskey Environmental assumes no liability resulting from errors or omissions in this document.