

McCourt Equipment, Inc.
5141 W State Highway 71
La Grange, Texas 78945



Office 979-242-5298
Fax 979-242-5292
Toll Free 888-838-9252

www.mccourtequipment.com

**USED LIPPMANN PORTABLE ELECTRIC 4248 HORIZONTAL SHAFT IMPACT CRUSHER
AND 6X20 TRIPLE DECK HORIZONTAL SCREEN SET UP IN A CLOSED CIRCUIT CONFIGURATION.
(Lippmann Combo Plant)**

Year: 2019
Serial Number: 2019-02123
Approx. Hours: 4511

- **VERY GOOD CONDITION**



(For set up illustration purposes only.)



(For set up illustration purposes only.)



(Actual current condition.)



(Actual current condition.)



(Actual current condition.)



(Actual current condition.)



(Actual current condition.)



(Actual current condition.)



(Actual current condition.)



(Actual current condition.)

McCourt Equipment, Inc.
5141 W State Highway 71
La Grange, Texas 78945



Office 979-242-5298
Fax 979-242-5292
Toll Free 888-838-9252

www.mccourtequipment.com

HP Requirements

Impactor Panel
Impactor: 250Hp
Feeder: 30Hp (VFD)
Magnet: 5Hp
Rear Discharge: 20Hp
Pan Feeder: x2 2.5
Return Conveyor: 10Hp
Grizzly By-Pass Conveyor: 7.5Hp

Screen Panel
Screen Return: 10Hp
Screen: 40Hp
Cross Conveyor #1: 7.5Hp
Cross Conveyor #2: 7.5Hp
Cross Conveyor #3: 7.5Hp
Underscreen Discharge: 20Hp
Off Plant #1: 30Hp
Off Plant #2: 30Hp
Off Plant #3: 30Hp

Plant HP: 420Hp






4800 w/620 IMPACT CRUSHER

The 4800 plant with the ability to mate up with a 6x20 Triple Deck Screen Plant makes this combination one of the most productive and flexible plants on the market. It's ideally suited to be fed with a loader for all types of material and shines when used in asphalt recycling due to the increased screen size and high reduction ratio. Increased production and reduced downtime are the results of industry customer recommendations being applied.

- An extra heavily ribbed steel frame- stress relieved after welding and before machining
- One piece steel pitman
- Heat-treated forged alloy steel eccentric shaft
- Oversized roller bearings on the pitman
- Spherical roller bearings on the frame
- Reversible manganese steel jaw dies and extensions
- Steel cheek plates
- Opposing wedge toggle tensioning system
- Grease lubricated
- Two heavy-duty flywheels, one grooved for V-belts

4800 w/620



SPECIFICATIONS

Impactor		Horsepower		Screen Plant		Transportation (lbs)	
Impactor	4248LP	Impact Crusher	250	Screen Size	6x20	Impactor Plant	
RPM	512	Feeder	30	Number of Decks	3	Tires	11R22.5
Discharge Conveyor	48"x44"	Discharge Conveyor	20	Screen Speed	810	Rear Axle	63,250
Operating Speed	314	Return Conveyor	10	Cross Conveyor	24"x10'	King Pin	45,750
Return Conveyor	24"x34"	Screen	40	Operating Speed	240	Total	111,000
Operating Speed	240	Cross Conveyor	7.5	Cross Conveyor	24"x10'	Screen Plant	
Pan Feeder	48"x72"	Underscreen Conveyor	20	Operating Speed	240	Tires	11R22.5
Operating Speed	1150	Return Conveyor	10	Underscreen Conveyor	54"x42'	Rear Axle	52,500
Feeder	47"x16'			Operating Speed	340	King Pin	23,250
Operating Speed	850Max			Return Conveyor	24"x42'	Total	75,750
				Operating Speed	272		

ADDITIONAL OPTIONS

- Hydraulic leveling jacks - (4) 70,000lb
- Six (6) Run-On Jack Legs
- NEMA - 12 motor control center
- Cross conveyor under grizzly
- Hydraulic folding hopper extensions
- Taper Wedge Lock
- Tire bulkheads

	4248LP			
	Setting (secondary apron to hammer tip clearance in inches)			
	1.75	2	2.5	3
(tons)	170-225	175-230	180-240	190-260
Maximum Feed Size (inches)	16	18	18	18
	6	8	8	8
	16	20	20	20